



FITTING INSTRUCTIONS

Part Number :- 501282
Part Description :- Ace Mounting
Fitting Location :- Left Dash



Make	Model	Bodystyle	From	To
Renault	D-Series	HGV	1/2015	Onw

Vehicle Details

Renault D-Series HGV 1/2015 - Onw

Instructions

1. Using a plastic trim removal tool carefully un-clip and remove the instrument binnacle surround trim and put it in a safe place.
2. Using the trim tool carefully un-clip the plastic cover from the top of the USB charging base that is located on the top of the dashboard above the switch panel, un-clip the trim starting from the most forward edge closest to the windscreen.
3. Un-clip and remove the power connector from charging base and then using a Torx T10 screwdriver remove the Three screws securing the charging base to the top of the dashboard, remove the charging base and put in a safe place.

Note: Step 2 could be slightly different for vehicles fitted with the optional tablet holder.

4. Use the trim tool to unclip the top of the heater control surround trim where the charging base was removed, then carefully pull the top of the trim forward slightly for access.

Note: The heater controls will pull forward with the trim panel which is secured at the bottom so you are not removing the trim only pulling the top forward to allow access.

5. Hook the bracket behind the heater control surround trim so the bracket is positioned to the right side of the centre air-vent. (See Image)
6. Position the bracket so the Two fixing holes rest up against the side of the plastic sub-structure behind where the heater surround trim locates.
7. Once bracket is located correctly drill through the two holes into the dashboard sub-structure using a 5mm drill bit.
Important Note: Check the nozzle of the pot rivet gun will fit through the hole in the bracket
before drilling the 5mm holes in the dashboard, it is also be possible to use self-tapping screws or machine screws & nuts to secure the bracket to the dashboard sub-structure.
8. Use a Pot rivet gun to firmly secure the bracket to side of the dashboard using the pot rivets provided.
9. Re-install the heater control surround trim
10. Re-install the USB charging base and re-connect the power connector.
11. Finally re-install the instrument binnacle surround trim.



Care should always be taken by the installer when installing this product. Nemesis is not liable for any damage caused to a vehicle by incorrect installation, use, modifications or repair by any 3rd party or yourself.
Tel: 01905 720199 email: sales@nemesis.ltd web: www.nemesisb2b.com